

## **TYRES**

Product group	Tyres	
Item number	10000495	
Valid tyre size	420 / 70 R 28	
LI / SI / PR	139 D / 136 E	
TL/TT	TL	
Brand	Bridgestone	
Tread pattern	VX-Tractor	





## **Notes and features**

- The Bridgestone VX-Tractor is radial tyre for tractors for combined use in the field and on the road.
- Its tractor tread pattern with extra high lug volume due to long and high lugs ensures good traction and slow wear.
- The rubber compound is particularly resistant to damage and wear.
- The carcass construction with reinforced sidewall and 6ply premium belt guarantees long life and puncture resistance even when driving with high air pressure.



## **Technical Informations**

Item number	10000495	
EAN	3286341340815	
Valid tyre size	420 / 70 R 28	
LI / SI / PR	139 D / 136 E	
TL/TT	TL	
Brand	Bridgestone	
Tread pattern	VX-Tractor	
Antistatic	No	
Tyre colour	Black	
ECE regulation number	ECE 106	
Nettogewicht [kg] (gültig)	99,31	
Recommended rim size	DW13	
Permitted rim size	DW12, W12, W13, DW14L, W14L	
Maximum air pressure [bar].	2,40	
Section width (mm)	430	
Outer diameter of tyre [mm].	1356	
Stat. radius (SLR) [mm]	621	
Speed Radius Index (SRI)	650	
Rolling circumference [mm].	4068	
Tread depth (mm)	47,0	
Number of lugs	19x2	
Tyre capacity 75% [ltr.]	201	
E-Ready	No	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
139 D	2430	65		2,40	
136 E	2240	70		2,40	