

## TYRES

Product group	Tyres
Item number	10000497
Valid tyre size	440 / 65 R 28
LI / SI / PR	138 D / 135 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor



**BRIDGESTONE**

## Notes and features

- The Bridgestone VX-Tractor is radial tyre for tractors for combined use in the field and on the road.
- Its tractor tread pattern with extra high lug volume due to long and high lugs ensures good traction and slow wear.
- The rubber compound is particularly resistant to damage and wear.
- The carcass construction with reinforced sidewall and 6-ply premium belt guarantees long life and puncture resistance even when driving with high air pressure.

## Technical Informations

Item number	10000497
EAN	3286341976014
Valid tyre size	440 / 65 R 28
LI / SI / PR	138 D / 135 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	92,72
Recommended rim size	DW14L
Permitted rim size	DW13, W13, W14L, W15L, DW15L
Maximum air pressure [bar].	2,40
Section width (mm)	425
Tread width (mm)	425
Outer diameter of tyre [mm].	1288
Stat. radius (SLR) [mm]	590
Speed Radius Index (SRI)	625
Rolling circumference [mm].	3890
Tread depth (mm)	45,5
Number of lugs	19x2
Tyre capacity 75% [litr.]	184
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
138 D	2360	65		2,40	
135 E	2180	70		2,40	