

TYRES

Product group	Tyres
Item number	10000508
Valid tyre size	460 / 85 R 30
LI / SI / PR	150 D / 147 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor



BRIDGESTONE

Notes and features

- The Bridgestone VX-Tractor is radial tyre for tractors for combined use in the field and on the road.
- Its tractor tread pattern with extra high lug volume due to long and high lugs ensures good traction and slow wear.
- The rubber compound is particularly resistant to damage and wear.
- The carcass construction with reinforced sidewall and 6-ply premium belt guarantees long life and puncture resistance even when driving with high air pressure.

Technical Informations

Item number	10000508
EAN	3286341697711
Valid tyre size	460 / 85 R 30
LI / SI / PR	150 D / 147 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	151,84
Recommended rim size	DW16L
Permitted rim size	DW15L, W15L, W16L
Maximum air pressure [bar].	2,40
Section width (mm)	482
Outer diameter of tyre [mm].	1542
Stat. radius (SLR) [mm]	711
Speed Radius Index (SRI)	725
Rolling circumference [mm].	4617
Tread depth (mm)	54,5
Number of lugs	19x2
Tyre capacity 75% [ltr.]	316
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
150 D	3350	65		2,40	
147 E	3075	70		2,40	