

TYRES

Product group	Tyres
Item number	10000509
Valid tyre size	480 / 70 R 30
LI / SI / PR	147 D / 144 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor



BRIDGESTONE

Notes and features

- The Bridgestone VX-Tractor is radial tyre for tractors for combined use in the field and on the road.
- Its tractor tread pattern with extra high lug volume due to long and high lugs ensures good traction and slow wear.
- The rubber compound is particularly resistant to damage and wear.
- The carcass construction with reinforced sidewall and 6-ply premium belt guarantees long life and puncture resistance even when driving with high air pressure.

Technical Informations

Item number	10000509
EAN	3286341338713
Valid tyre size	480 / 70 R 30
LI / SI / PR	147 D / 144 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	134,31
Recommended rim size	DW15L
Permitted rim size	DW14L, W14L, W15L, W16L, DW16L
Maximum air pressure [bar].	2,40
Section width (mm)	490
Outer diameter of tyre [mm].	1481
Stat. radius (SLR) [mm]	678
Speed Radius Index (SRI)	700
Rolling circumference [mm].	4442
Tread depth (mm)	50,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	284
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
147 D	3075	65		2,40	
144 E	2800	70		2,40	