

## **RIMS**

Product group	Rims
Item number	10000515
Valid rim size	AG 20.00 x 26.5 TH2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	+80
Rim colour	Silver
Brand	GKN
Rim series	Profiline
Sonderpostenkategorie	Remaining stock





Technical Informations		
Load capacity of rim 1 [kg]	8840	
Speed Rims 1 [km/h]	40	
Load capacity of rim 2 [kg]	6500	
Speed Rims 2 [km/h]	65	
Nettogewicht [kg] (gültig)	85,00	
Hump	TH2	
RAL	RAL9006	
Cavity Sealed	No	
Verschweißung beidseitig	No	
Ventilation holes	No	
Number of bolt holes	10	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Preassembled valve	No
TPMS-kompatibles Ventil	No