

TYRES

Product group	Tyres
Item number	10000520
Valid tyre size	500 / 80 R 28
LI / SI / PR	162 A8 / 182 A8
TL/TT	TL
Brand	Mitas
Tread pattern	SFT IMP
Sonderpostenkategorie	Remaining stock



Mitas

Technical Informations

Item number	10000520
EAN	4040658104176
Valid tyre size	500 / 80 R 28
LI / SI / PR	162 A8 / 182 A8
TL/TT	TL
Brand	Mitas
Tread pattern	SFT IMP
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	136,00
Recommended rim size	16

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Permitted rim size	15
Maximum air pressure [bar].	3,20
Section width (mm)	517
Outer diameter of tyre [mm].	1495
Stat. radius (SLR) [mm]	635
Rolling circumference [mm].	4355
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 A8	4750	40		3,20	
182 A8	8500	40			

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.