

TYRES

Product group	Tyres
Item number	10000528
Valid tyre size	520 / 70 R 38
LI / SI / PR	155 D / 152 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor



BRIDGESTONE

Notes and features

- The Bridgestone VX-Tractor is radial tyre for tractors for combined use in the field and on the road.
- Its tractor tread pattern with extra high lug volume due to long and high lugs ensures good traction and slow wear.
- The rubber compound is particularly resistant to damage and wear.
- The carcass construction with reinforced sidewall and 6-ply premium belt guarantees long life and puncture resistance even when driving with high air pressure.

Technical Informations

Item number	10000528
EAN	3286341338812
Valid tyre size	520 / 70 R 38
LI / SI / PR	155 D / 152 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	203,58
Recommended rim size	DW16L
Permitted rim size	W16L, DW18L, W18L
Maximum air pressure [bar].	2,40
Section width (mm)	521
Outer diameter of tyre [mm].	1746
Stat. radius (SLR) [mm]	788
Speed Radius Index (SRI)	825
Rolling circumference [mm].	5211
Tread depth (mm)	56,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	392
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 D	3875	65		2,40	
152 E	3550	70		2,40	