

TYRES

| | |
|-----------------|---------------|
| Product group | Tyres |
| Item number | 10000530 |
| Valid tyre size | 540 / 65 R 38 |
| LI / SI / PR | 153 D / 150 E |
| TL/TT | TL |
| Brand | Bridgestone |
| Tread pattern | VX-Tractor |



BRIDGESTONE

Notes and features

- The Bridgestone VX-Tractor is radial tyre for tractors for combined use in the field and on the road.
- Its tractor tread pattern with extra high lug volume due to long and high lugs ensures good traction and slow wear.
- The rubber compound is particularly resistant to damage and wear.
- The carcass construction with reinforced sidewall and 6-ply premium belt guarantees long life and puncture resistance even when driving with high air pressure.

Technical Informations

| | |
|------------------------------|-------------------|
| Item number | 10000530 |
| EAN | 3286341339017 |
| Valid tyre size | 540 / 65 R 38 |
| LI / SI / PR | 153 D / 150 E |
| TL/TT | TL |
| Brand | Bridgestone |
| Tread pattern | VX-Tractor |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 172,77 |
| Recommended rim size | DW16L |
| Permitted rim size | W16L, DW18L, W18L |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 523 |
| Outer diameter of tyre [mm]. | 1671 |
| Stat. radius (SLR) [mm] | 757 |
| Speed Radius Index (SRI) | 800 |
| Rolling circumference [mm]. | 4990 |
| Tread depth (mm) | 51,0 |
| Number of lugs | 21x2 |
| Tyre capacity 75% [ltr.] | 362 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 153 D | 3650 | 65 | | 2,40 | |
| 150 E | 3350 | 70 | | 2,40 | |