

TYRES

Product group	Tyres
Item number	10000530
Valid tyre size	540 / 65 R 38
LI / SI / PR	153 D / 150 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor



BRIDGESTONE

Notes and features

- The Bridgestone VX-Tractor is radial tyre for tractors for combined use in the field and on the road.
- Its tractor tread pattern with extra high lug volume due to long and high lugs ensures good traction and slow wear.
- The rubber compound is particularly resistant to damage and wear.
- The carcass construction with reinforced sidewall and 6-ply premium belt guarantees long life and puncture resistance even when driving with high air pressure.

Technical Informations

Item number	10000530
EAN	3286341339017
Valid tyre size	540 / 65 R 38
LI / SI / PR	153 D / 150 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	172,77
Recommended rim size	DW16L
Permitted rim size	W16L, DW18L, W18L
Maximum air pressure [bar].	2,40
Section width (mm)	523
Outer diameter of tyre [mm].	1671
Stat. radius (SLR) [mm]	757
Speed Radius Index (SRI)	800
Rolling circumference [mm].	4990
Tread depth (mm)	51,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	362
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 D	3650	65		2,40	
150 E	3350	70		2,40	