

## TYRES

|                 |               |
|-----------------|---------------|
| Product group   | Tyres         |
| Item number     | 10000531      |
| Valid tyre size | 580 / 70 R 38 |
| LI / SI / PR    | 160 D / 157 E |
| TL/TT           | TL            |
| Brand           | Bridgestone   |
| Tread pattern   | VX-Tractor    |



**BRIDGESTONE**

## Notes and features

- The Bridgestone VX-Tractor is radial tyre for tractors for combined use in the field and on the road.
- Its tractor tread pattern with extra high lug volume due to long and high lugs ensures good traction and slow wear.
- The rubber compound is particularly resistant to damage and wear.
- The carcass construction with reinforced sidewall and 6-ply premium belt guarantees long life and puncture resistance even when driving with high air pressure.

## Technical Informations

|                              |               |
|------------------------------|---------------|
| Item number                  | 10000531      |
| EAN                          | 3286341343212 |
| Valid tyre size              | 580 / 70 R 38 |
| LI / SI / PR                 | 160 D / 157 E |
| TL/TT                        | TL            |
| Brand                        | Bridgestone   |
| Tread pattern                | VX-Tractor    |
| Antistatic                   | No            |
| Tyre colour                  | Black         |
| ECE regulation number        | ECE 106       |
| Nettogewicht [kg] (gültig)   | 248,12        |
| Recommended rim size         | DW18L         |
| Permitted rim size           | W18L          |
| Maximum air pressure [bar].  | 2,40          |
| Section width (mm)           | 585           |
| Tread width (mm)             | 585           |
| Outer diameter of tyre [mm]. | 1812          |
| Stat. radius (SLR) [mm]      | 819           |
| Speed Radius Index (SRI)     | 875           |
| Rolling circumference [mm].  | 5408          |
| Tread depth (mm)             | 60,0          |
| Number of lugs               | 20x2          |
| Tyre capacity 75% [litr.]    | 513           |
| E-Ready                      | No            |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 160 D | 4500               | 65           |               | 2,40                     |              |
| 157 E | 4125               | 70           |               | 2,40                     |              |