

TYRES

Product group	Tyres
Item number	10000531
Valid tyre size	580 / 70 R 38
LI / SI / PR	160 D / 157 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor



BRIDGESTONE

Notes and features

- The Bridgestone VX-Tractor is radial tyre for tractors for combined use in the field and on the road.
- Its tractor tread pattern with extra high lug volume due to long and high lugs ensures good traction and slow wear.
- The rubber compound is particularly resistant to damage and wear.
- The carcass construction with reinforced sidewall and 6-ply premium belt guarantees long life and puncture resistance even when driving with high air pressure.

Technical Informations

Item number	10000531
EAN	3286341343212
Valid tyre size	580 / 70 R 38
LI / SI / PR	160 D / 157 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	248,12
Recommended rim size	DW18L
Permitted rim size	W18L
Maximum air pressure [bar].	2,40
Section width (mm)	585
Tread width (mm)	585
Outer diameter of tyre [mm].	1812
Stat. radius (SLR) [mm]	819
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5408
Tread depth (mm)	60,0
Number of lugs	20x2
Tyre capacity 75% [litr.]	513
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 D	4500	65		2,40	
157 E	4125	70		2,40	