

## TYRES

Product group	Tyres
Item number	10000532
Valid tyre size	600 / 65 R 38
LI / SI / PR	159 D / 156 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor



**BRIDGESTONE**

## Notes and features

- The Bridgestone VX-Tractor is radial tyre for tractors for combined use in the field and on the road.
- Its tractor tread pattern with extra high lug volume due to long and high lugs ensures good traction and slow wear.
- The rubber compound is particularly resistant to damage and wear.
- The carcass construction with reinforced sidewall and 6-ply premium belt guarantees long life and puncture resistance even when driving with high air pressure.

## Technical Informations

Item number	10000532
EAN	3286341339116
Valid tyre size	600 / 65 R 38
LI / SI / PR	159 D / 156 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	231,16
Recommended rim size	DW20B
Permitted rim size	DW18L, W18L
Maximum air pressure [bar].	2,40
Section width (mm)	594
Outer diameter of tyre [mm].	1747
Stat. radius (SLR) [mm]	774
Speed Radius Index (SRI)	825
Rolling circumference [mm].	5214
Tread depth (mm)	57,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	462
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 D	4375	65		2,40	
156 E	4000	70		2,40	