

TYRES

Product group	Tyres
Item number	10000542
Valid tyre size	710 / 70 R 42
LI / SI / PR	173 D / 170 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor





Notes and features

- The Bridgestone VX-Tractor is radial tyre for tractors for combined use in the field and on the road.
- Its tractor tread pattern with extra high lug volume due to long and high lugs ensures good traction and slow wear.
- The rubber compound is particularly resistant to damage and wear.
- The carcass construction with reinforced sidewall and 6ply premium belt guarantees long life and puncture resistance even when driving with high air pressure.



Technical Informations

Item number	10000542
EAN	3286341343113
Valid tyre size	710 / 70 R 42
LI / SI / PR	173 D / 170 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	361,11
Recommended rim size	DW23B
Permitted rim size	DW25B
Maximum air pressure [bar].	2,40
Section width (mm)	732
Outer diameter of tyre [mm].	2096
Stat. radius (SLR) [mm]	942
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6288
Tread depth (mm)	64,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	825
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 D	6500	65		2,40	
170 E	6000	70		2,40	