

TYRES

Product group	Tyres
Item number	10000549
Valid tyre size	VF 650 / 60 R 34 NRO
LI / SI / PR	165 D / 162 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Tractor



Bohnenkamp
■ ■ ● Moving Professionals

BRIDGESTONE

Notes and features

- High load capacity thanks to VF-Ultraflex technology.
- Low tyre pressure, even with heavy loads.
- Very good traction und high ride comfort.
- Thanks to NRO technology (Narrow Rim Option), the tyre can be mounted on a narrower rim than other VF or IF tyres of the same dimension.

Technical Informations

Item number	10000549
EAN	3286341046410
Valid tyre size	VF 650 / 60 R 34 NRO
LI / SI / PR	165 D / 162 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Tractor
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	219,44
Recommended rim size	DW23B
Permitted rim size	DW21B, DW20B
Maximum air pressure [bar].	1,60
Section width (mm)	650
Outer diameter of tyre [mm].	1644
Stat. radius (SLR) [mm]	721
Speed Radius Index (SRI)	775
Rolling circumference [mm].	4885
Tread depth (mm)	58,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	502
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
165 D	5150	65		1,60	
162 E	4750	70		1,60	