

## TYRES

Product group	Tyres
Item number	10000551
Valid tyre size	VF 650 / 65 R 34 NRO
LI / SI / PR	167 D / 164 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Tractor



Bohnenkamp  
■ ■ ● Moving Professionals

**BRIDGESTONE**

## Notes and features

- High load capacity thanks to VF-Ultraflex technology.
- Low tyre pressure, even with heavy loads.
- Very good traction und high ride comfort.
- Thanks to NRO technology (Narrow Rim Option), the tyre can be mounted on a narrower rim than other VF or IF tyres of the same dimension.

## Technical Informations

Item number	10000551
EAN	3286341046618
Valid tyre size	VF 650 / 65 R 34 NRO
LI / SI / PR	167 D / 164 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Tractor
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	221,55
Recommended rim size	DW23B
Permitted rim size	DW21B, DW20B
Maximum air pressure [bar].	1,60
Section width (mm)	658
Outer diameter of tyre [mm].	1702
Stat. radius (SLR) [mm]	725
Speed Radius Index (SRI)	825
Rolling circumference [mm].	5131
Tread depth (mm)	58,0
Tyre capacity 75% [ltr.]	555
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
167 D	5450	65		1,60	
164 E	5000	70		1,60	