

TYRES

Product group	Tyres
Item number	10000552
Valid tyre size	VF 620 / 70 R 42
LI / SI / PR	172 D / 169 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Tractor



BRIDGESTONE

Notes and features

- High load capacity thanks to VF-Ultraflex technology.
- Low tyre pressure, even with heavy loads.
- Very good traction und high ride comfort.
- Thanks to NRO technology (Narrow Rim Option), the tyre can be mounted on a narrower rim than other VF or IF tyres of the same dimension.

Technical Informations

Item number	10000552
EAN	3286341046014
Valid tyre size	VF 620 / 70 R 42
LI / SI / PR	172 D / 169 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Tractor
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	268,27
Recommended rim size	DW23B
Permitted rim size	DW20B, DW21B
Maximum air pressure [bar].	1,60
Section width (mm)	654
Outer diameter of tyre [mm].	1935
Stat. radius (SLR) [mm]	824
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5757
Tread depth (mm)	60,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	641
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 D	6300	65		1,60	
169 E	5800	70		1,60	