

TYRES

Product group	Tyres
Item number	10000554
Valid tyre size	VF 620 / 75 R 26 CFO
LI / SI / PR	172 A8
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Combine



BRIDGESTONE

Notes and features

- The Bridgestone VT Combine is a radial tyre for harvesting vehicles.
- The lug design and the large contact area ensure very good traction with the greatest possible ground protection.
- Due to the carcass construction, high load capacities are possible with low air pressure, ensuring reduced soil compaction.
- The strong so-called S-Line bead guarantees long service life even under difficult conditions and heavy loads on the tyre.

Technical Informations

Item number	10000554
EAN	3286340855310
Valid tyre size	VF 620 / 75 R 26 CFO
LI / SI / PR	172 A8
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Combine
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	168,62
Recommended rim size	DW20B
Maximum air pressure [bar].	2,40
Tread width (mm)	581
Outer diameter of tyre [mm].	1575
Stat. radius (SLR) [mm]	683
Speed Radius Index (SRI)	750
Rolling circumference [mm].	4709
Tread depth (mm)	45,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	433
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 A8	6300	40		2,40	