

TYRES

Product group	Tyres
Item number	10000555
Valid tyre size	VF 750 / 65 R 26 CFO
LI / SI / PR	177 A8
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Combine



BRIDGESTONE

Notes and features

- The Bridgestone VT Combine is a radial tyre for harvesting vehicles.
- The lug design and the large contact area ensure very good traction with the greatest possible ground protection.
- Due to the carcass construction, high load capacities are possible with low air pressure, ensuring reduced soil compaction.
- The strong so-called S-Line bead guarantees long service life even under difficult conditions and heavy loads on the tyre.

Technical Informations

Item number	10000555
EAN	3286340855518
Valid tyre size	VF 750 / 65 R 26 CFO
LI / SI / PR	177 A8
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Combine
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	207,19
Recommended rim size	DW25B
Maximum air pressure [bar].	2,40
Section width (mm)	708
Outer diameter of tyre [mm].	1628
Stat. radius (SLR) [mm]	701
Speed Radius Index (SRI)	775
Rolling circumference [mm].	4867
Tread depth (mm)	48,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	599
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
177 A8	7300	40		2,40	