

TYRES

| | |
|-----------------|----------------------|
| Product group | Tyres |
| Item number | 10000557 |
| Valid tyre size | IF 650 / 75 R 32 CFO |
| LI / SI / PR | 173 A8 |
| TL/TT | TL |
| Brand | Bridgestone |
| Tread pattern | VT Combine |



BRIDGESTONE

Notes and features

- The Bridgestone VT Combine is a radial tyre for harvesting vehicles.
- The lug design and the large contact area ensure very good traction with the greatest possible ground protection.
- Due to the carcass construction, high load capacities are possible with low air pressure, ensuring reduced soil compaction.
- The strong so-called S-Line bead guarantees long service life even under difficult conditions and heavy loads on the tyre.

Technical Informations

| | |
|------------------------------|----------------------|
| Item number | 10000557 |
| EAN | 3286340854511 |
| Valid tyre size | IF 650 / 75 R 32 CFO |
| LI / SI / PR | 173 A8 |
| TL/TT | TL |
| Brand | Bridgestone |
| Tread pattern | VT Combine |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 234,42 |
| Recommended rim size | DW21B |
| Permitted rim size | DW23B |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 646 |
| Outer diameter of tyre [mm]. | 1770 |
| Stat. radius (SLR) [mm] | 775 |
| Speed Radius Index (SRI) | 850 |
| Rolling circumference [mm]. | 5292 |
| Tread depth (mm) | 51,0 |
| Number of lugs | 20x2 |
| Tyre capacity 75% [ltr.] | 668 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 173 A8 | 6500 | 40 | | 2,40 | |