

TYRES

Product group	Tyres
Item number	10000557
Valid tyre size	IF 650 / 75 R 32 CFO
LI / SI / PR	173 A8
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Combine



BRIDGESTONE

Notes and features

- The Bridgestone VT Combine is a radial tyre for harvesting vehicles.
- The lug design and the large contact area ensure very good traction with the greatest possible ground protection.
- Due to the carcass construction, high load capacities are possible with low air pressure, ensuring reduced soil compaction.
- The strong so-called S-Line bead guarantees long service life even under difficult conditions and heavy loads on the tyre.

Technical Informations

Item number	10000557
EAN	3286340854511
Valid tyre size	IF 650 / 75 R 32 CFO
LI / SI / PR	173 A8
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Combine
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	234,42
Recommended rim size	DW21B
Permitted rim size	DW23B
Maximum air pressure [bar].	2,40
Section width (mm)	646
Outer diameter of tyre [mm].	1770
Stat. radius (SLR) [mm]	775
Speed Radius Index (SRI)	850
Rolling circumference [mm].	5292
Tread depth (mm)	51,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	668
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 A8	6500	40		2,40	