

## TYRES

Product group	Tyres
Item number	10000563
Valid tyre size	IF 800 / 70 R 38 CFO
LI / SI / PR	184 A8
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Combine



**BRIDGESTONE**

## Notes and features

- The Bridgestone VT Combine is a radial tyre for harvesting vehicles.
- The lug design and the large contact area ensure very good traction with the greatest possible ground protection.
- Due to the carcass construction, high load capacities are possible with low air pressure, ensuring reduced soil compaction.
- The strong so-called S-Line bead guarantees long service life even under difficult conditions and heavy loads on the tyre.

## Technical Informations

Item number	10000563
EAN	3286340854818
Valid tyre size	IF 800 / 70 R 38 CFO
LI / SI / PR	184 A8
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Combine
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	364,91
Recommended rim size	DW27B
Maximum air pressure [bar].	2,40
Section width (mm)	787
Outer diameter of tyre [mm].	2053
Stat. radius (SLR) [mm]	899
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6127
Tread depth (mm)	58,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	978
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
184 A8	9000	40		2,40	