

TYRES

Product group	Tyres	
Item number	10000573	
Valid tyre size	480 / 70 R 24	
LI/SI/PR	138 D / 135 E	
TL/TT	TL	
Brand	Firestone	
Tread pattern	Performer 70	
Sonderpostenkategorie	Damaged	
type of damage	Cut in the flank,Dismounted	



Notes and features

- Unique double-angle lug technology.
- Large ground contact area due to stronger deflection and flatter tread pattern contour.
- Increased ride comfort.



Technical Informations

Item number	10000573
EAN	4040658104312
Valid tyre size	480 / 70 R 24
LI / SI / PR	138 D / 135 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 70
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	98,80
Recommended rim size	15
Permitted rim size	14, 16
Maximum air pressure [bar].	1,60
Section width (mm)	482
Outer diameter of tyre [mm].	1323
Stat. radius (SLR) [mm]	595
Rolling circumference [mm].	3969
Tread depth (mm)	46,5
Number of lugs	18x2
Tyre capacity 75% [ltr.]	264
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
138 D	2360	65		1,60	
135 E	2180	70		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.