

WHEELS

Product group	Wheels
Item number	10000577
Valid wheel size	365 / 70 R 18
Brand	BKT
Tread pattern	Multimax MP 513
Valid rim size	11 x 18
Rim connection	8/221/275
Bolt hole design	A3
Offset (mm)	-10
Rim colour	Silver
Load capacity complete wheel [kg]	2060
Speed complete wheel [km/h]	90
Nettogewicht [kg] (gültig)	78,28
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15735226
LI / SI / PR	133 G
Load capacity 1 [kg]	2060
Speed 1 [km/h].	90
Maximum air pressure [bar].	3,75
TL/TT	TL
Tyre colour	Black
E-Ready	No

Antistatic	No
ECE regulation number	ECE 54
Section width (mm)	360
Stat. radius (SLR) [mm]	448
Rolling circumference [mm].	2954
Tread depth (mm)	28,5
Number of lugs	18x2
Assembly Item no. Rim	• 33060097
Load capacity of rim 1 [kg]	3850
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3150
Speed Rims 2 [km/h]	90
Maximum speed [km/h].	90
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	8
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	27
Bolt hole design EUWA	B22 ES 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig

Hump	kein Hump
Valve protection	VSH
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade