

TYRES

| | |
|-----------------------|------------------------|
| Product group | Tyres |
| Item number | 10000579 |
| Valid tyre size | 540 / 65 R 30 |
| LI / SI / PR | 143 D / 140 E |
| TL/TT | TL |
| Brand | Firestone |
| Tread pattern | Maxi Traction 65 |
| Sonderpostenkategorie | Damaged |
| type of damage | Flap damage,Dismounted |



Notes and features

- Agricultural tyre for high-performance tractors.
- Very good traction in fields.
- Excellent ride comfort on the road.
- Very low soil compaction.

Technical Informations

| | |
|------------------------------|------------------|
| Item number | 10000579 |
| EAN | 4040658104374 |
| Valid tyre size | 540 / 65 R 30 |
| LI / SI / PR | 143 D / 140 E |
| TL/TT | TL |
| Brand | Firestone |
| Tread pattern | Maxi Traction 65 |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 134,86 |
| Recommended rim size | 16 |
| Permitted rim size | 18 |
| Maximum air pressure [bar]. | 1,60 |
| Section width (mm) | 521 |
| Outer diameter of tyre [mm]. | 1462 |
| Stat. radius (SLR) [mm] | 659 |
| Rolling circumference [mm]. | 4386 |
| Tread depth (mm) | 45,0 |
| Number of lugs | 20x2 |
| Tyre capacity 75% [ltr.] | 333 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 143 D | 2725 | 65 | | 1,60 | |
| 140 E | 2500 | 70 | | 1,60 | |