

TYRES

Product group	Tyres
Item number	10000585
Valid tyre size	IF 650 / 60 R 34
LI / SI / PR	165 D
TL/TT	TL
Brand	Michelin
Tread pattern	AxioBib
Sonderpostenkategorie	Damaged
type of damage	Dismounted,Stud damage



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Low fuel consumption due to very good traction.
- Low tyre inflation pressure even when under heavy load.
- High load capacity thanks to Ultraflex technology.

Technical Informations

Item number	10000585
EAN	4040658104435
Valid tyre size	IF 650 / 60 R 34
LI / SI / PR	165 D
TL/TT	TL
Brand	Michelin
Tread pattern	AxioBib
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	215,00
Recommended rim size	23
Permitted rim size	21, 24
Maximum air pressure [bar].	2,40
Section width (mm)	653
Outer diameter of tyre [mm].	1661
Stat. radius (SLR) [mm]	745
Rolling circumference [mm].	4933
Tread depth (mm)	58,0
Tyre capacity 75% [litr.]	500
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
165 D	5150	65		2,40	