

TYRES

Product group	Tyres
Item number	10000591
Valid tyre size	IF 650 / 60 R 34
LI / SI / PR	165 D
TL/TT	TL
Brand	Michelin
Tread pattern	AxioBib
Sonderpostenkategorie	Disassambled
type of damage	Dismounted





Notes and features

- Low fuel consumption due to very good traction.
- Low tyre inflation pressure even when under heavy load.
- High load capacity thanks to Ultraflex technology.



Technical Informations

Item number	10000591
EAN	4040658104497
Valid tyre size	IF 650 / 60 R 34
LI / SI / PR	165 D
TL/TT	TL
Brand	Michelin
Tread pattern	AxioBib
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	215,00
Recommended rim size	23
Permitted rim size	21, 24
Maximum air pressure [bar].	2,40
Section width (mm)	653
Outer diameter of tyre [mm].	1661
Stat. radius (SLR) [mm]	745
Rolling circumference [mm].	4933
Tread depth (mm)	58,0
Tyre capacity 75% [ltr.]	500
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
165 D	5150	65		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.