

RIMS

Product group	Rims
Item number	10000606
Valid rim size	8.0 - 20
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+120
Half centre distance (HMA) [mm]	134
Rim colour	Black
Brand	Jamak



Technical Informations

Load capacity of rim 1 [kg]	5025
Speed Rims 1 [km/h]	20
Load capacity of rim 2 [kg]	3850
Speed Rims 2 [km/h]	40
Load capacity of rim 3 [kg]	7035
Speed Rims 3 [km/h]	5
Load capacity of rim 4 [kg]	6030
Speed of wheels 4 [km/h].	10
Maximum speed [km/h].	40
Maximum air pressure [bar].	9,00
Type of drive	Towed axle

Nettogewicht [kg] (gültig)	51,70
Hump	kein Hump
Single / multi-part	mehrteilig
Quantity multi-piece	three-part
Rim material	steel
RAL	RAL9005
Cavity Sealed	No
Rim design industry	Standard
Disc thickness [mm]	12
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	Internal Valve
Valve hole diameter [mm]	16x102
Preassembled valve	No
TPMS-kompatibles Ventil	No