

WHEELS

Product group	Wheels
Item number	10000609
Valid wheel size	500 / 70 R 24
Brand	Alliance
Tread pattern	Agro Industrial 580
Valid rim size	DW 16 L x 24
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	+15
Load capacity complete wheel [kg]	5000
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	173,28
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



 **ALLIANCE**

Technical Informations

Assembly Item no. Tyres	• 15285321
LI / SI / PR	164 A8 / 164 B
Load capacity 1 [kg]	5000
Speed 1 [km/h].	40
Load capacity 2 [kg]	5000
Speed 2 [km/h].	50
Maximum air pressure [bar].	4,00
TL/TT	TL
Tyre colour	Black

E-Ready	No
Carcass properties	Steel Belted
Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	505
Stat. radius (SLR) [mm]	600
Rolling circumference [mm].	3900
Tread depth (mm)	40,0
Assembly Item no. Rim	• 10000348
Load capacity of rim 1 [kg]	5200
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3850
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	10
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Bolt hole design EUWA	B22 ES 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC
Rim material	steel
Rim colour (manufacturer's designation)	Fendt Terra - red
Valve seat	External Valve
Disc thickness [mm]	12

Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Valve protection	VSH
Cavity Sealed	No
Knurling	with knurling
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade