

WHEELS

Product group	Wheels
Item number	10000609
Valid wheel size	500 / 70 R 24
Brand	Alliance
Tread pattern	Agro Industrial 580
Valid rim size	DW 16 L x 24
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	+15
Load capacity complete wheel [kg]	5000
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15285321
LI / SI / PR	164 A8 / 164 B
Load capacity 1 [kg]	5000
Speed 1 [km/h].	40
Load capacity 2 [kg]	5000
Speed 2 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	173,28
ECE regulation number	ECE 106
Section width (mm)	505

Stat. radius (SLR) [mm]	600
Rolling circumference [mm].	3900
Tread depth (mm)	40,0
E-Ready	No
Assembly Item no. Rim	• 10000348
Load capacity of rim 1 [kg]	5200
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3850
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	4,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
Rim colour (manufacturer's designation)	Fendt Terra - red
Cavity Sealed	No
Disc thickness [mm]	12
Knurling	with knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere

Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade