

TYRES

Product group	Tyres	
Item number	10000614	
Valid tyre size	480 / 80 R 46	
LI / SI / PR	176 A8 / 176 B	
TL/TT	TL	
Brand	Alliance	
Tread pattern	FarmPRO II	
Sonderpostenkategorie	Damaged	
type of damage	Dismounted,Flap damage	





Notes and features

- 70 series agricultural tyre for tractors in the low- to medium-power range up to approx. 180 hp (except 710 width).
- All-round tyre for use on farmland and grassland.
- R-1W drive tread pattern with high multi-angle lugs ensures good traction on wet ground.
- Reinforced beads and sidewalls as well as a wide lug contact area in the centre provide high ride comfort.



Technical Informations

Item number	10000614
EAN	4040658104725
Valid tyre size	480 / 80 R 46
LI / SI / PR	176 A8 / 176 B
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO II
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	178,30
Recommended rim size	16
Maximum air pressure [bar].	2,40
Section width (mm)	479
Outer diameter of tyre [mm].	1960
Stat. radius (SLR) [mm]	880
Rolling circumference [mm].	5840
Tread depth (mm)	50,0
Tyre capacity 75% [ltr.]	401
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 A8	7100	40		2,40	
176 B	7100	50		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.