

TYRES

Product group	Tyres
Item number	10000617
Valid tyre size	380 / 85 R 24
LI / SI / PR	131D / 128 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85
Sonderpostenkategorie	Disassembled
type of damage	Dismounted



Bohnenkamp
■ ■ ● Moving Professionals

Notes and features

- Narrow tyre for maintenance of row crops.
- High load capacity.
- Outstanding driving dynamics on the road.
- Very good traction and self-cleaning.
- Long service life.

Technical Informations

Item number	10000617
EAN	4040658104749
Valid tyre size	380 / 85 R 24
LI / SI / PR	131D / 128 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	70,50
Recommended rim size	13
Permitted rim size	11, 12
Maximum air pressure [bar].	1,60
Section width (mm)	403
Outer diameter of tyre [mm].	1257
Stat. radius (SLR) [mm]	564
Rolling circumference [mm].	3771
Tread depth (mm)	43,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	180
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
131 D	1950	65		1,60	
128 E	1800	70		1,60	