

## **TYRES**

Product group	Tyres	
Item number	10000621	
Valid tyre size	520 / 85 R 42	
LI / SI / PR	162 A8 / 162 B	
TL/TT	TL	
Brand	Michelin	
Tread pattern	AgriBib 2	
Sonderpostenkategorie	Damaged	
type of damage	Dismounted,Scratcher in the flank	





## Notes and features

- The Michelin Axiobib 2 is designed for tractors within a performance range of 60 to 170 hp.
- The new optimised tread with a lug angle of 45° offers very good traction transmission to the ground.
- Its particularly high tread depth ensures a long service life for the tyre.
- Thanks to the additional rubber lip along the tread centre, the tyre offers very good self-cleaning properties.
- The angle of the lugs and a rubber reinforcement on the tyre shoulder deflect stubble and protect the tyre from damage.



## **Technical Informations**

Item number	10000621
EAN	4040658104787
Valid tyre size	520 / 85 R 42
LI / SI / PR	162 A8 / 162 B
TL/TT	TL
Brand	Michelin
Tread pattern	AgriBib 2
Antistatic	No No
Tyre colour	Black
Nettogewicht [kg] (gültig)	195,00
Recommended rim size	18
Maximum air pressure [bar].	2,40
Section width (mm)	536
Outer diameter of tyre [mm].	1951
Stat. radius (SLR) [mm]	886
Rolling circumference [mm].	5810
Tread depth (mm)	56,0
Number of lugs	24x2
Tyre capacity 75% [ltr.]	545
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 A8	4750	40		2,40	
162 B	4750	50		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.