Bohnenkamp Moving Professionals

05.02.2025

TYRES

Product group	Tyres	
Item number	10000623	
Valid tyre size	VF 800 / 70 R 38	
LI / SI / PR	187 D / 184 E	
TL/TT	TL	
Brand	Michelin	
Tread pattern	AxioBib 2	
Sonderpostenkategorie	Damaged	
type of damage	Dismounted,Flap damage	



Notes and features

- The Michelin Axiobib 2 is suitable for tractors from 160 hp up to 550 hp.
- The VF tyre with its Ultraflex technology enables increased load capacity by up to 40%.
- Furthermore, the tyre is characterised by its low inflation pressure and excellent traction in the field.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10000623
EAN	4040658104800
Valid tyre size	VF 800 / 70 R 38
LI / SI / PR	187 D / 184 E
TL/TT	ть
Brand	Michelin
Tread pattern	AxioBib 2
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	398,00
Recommended rim size	DW27B
Permitted rim size	DW25B
Maximum air pressure [bar].	2,00
Section width (mm)	821
Outer diameter of tyre [mm].	2072
Stat. radius (SLR) [mm]	891
Rolling circumference [mm].	6096
Tread depth (mm)	63,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	1073
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
187 D	9750	65		2,00	
184 E	9000	70		2,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.