

TYRES

Product group	Tyres
Item number	10000624
Valid tyre size	320 / 90 R 50
LI / SI / PR	150 A8 / 150 B
TL/TT	TL
Brand	Michelin
Tread pattern	AgriBib
Sonderpostenkategorie	DOT
type of damage	DOT





Notes and features

- Ideal for medium-performance tractors.
- Enormous traction with low soil compaction.
- Excellent ride comfort.
- Long service life due to very high tread lugs.



Technical Informations

Item number	10000624
EAN	4040658104817
Valid tyre size	320 / 90 R 50
LI / SI / PR	150 A8 / 150 B
TL/TT	TL
Brand	Michelin
Tread pattern	AgriBib
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	112,00
Recommended rim size	10
Maximum air pressure [bar].	3,60
Section width (mm)	314
Outer diameter of tyre [mm].	1847
Stat. radius (SLR) [mm]	862
Rolling circumference [mm].	5539
Tread depth (mm)	39,0
Number of lugs	34x2
Tyre capacity 75% [ltr.]	226
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
150 A8	3350	40		3,60	
150 B	3350	50		3,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.