

TYRES

Product group	Tyres	
Item number	10000626	
Valid tyre size	650 / 65 R 38	
LI / SI / PR	160 A8 / 157 D	
TL/TT	TL	
Brand	Mitas	
Tread pattern	AC 65	
Sonderpostenkategorie	Damaged	
type of damage	Dismounted,Stud damage	



Mitas

Notes and features

- The AC 65 is a powerful all-round wide tyre for use in the field and on the road.
- Thanks to its wide contact area, the soil is protected effectively.
- The wear-resistant rubber compound ensures a long service life.
- The tyre is characterised by a large air volume, guaranteeing a high transport performance.



Technical Informations

Item number	10000626
	4040658104831
EAN	4040038104831
Valid tyre size	650 / 65 R 38
LI / SI / PR	160 A8 / 157 D
TL/TT	TL
Brand	Mitas
Tread pattern	AC 65
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	215,00
Recommended rim size	18
Permitted rim size	20
Maximum air pressure [bar].	1,60
Section width (mm)	618
Outer diameter of tyre [mm].	1828
Stat. radius (SLR) [mm]	810
Rolling circumference [mm].	5416
Tread depth (mm)	53,0
Number of lugs	22x2
Lug width (mm)	44
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 A8	4500	40		1,60	
157 D	4125	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.