

## **TYRES**

Product group	Tyres
Item number	10000633
Valid tyre size	500 / 80 R 28
LI / SI / PR	164 A8 / 176 A8
TL/TT	TL
Brand	Mitas
Tread pattern	SFT IMP
Sonderpostenkategorie	Damaged
type of damage	Dismounted,Crack in the tread



Mitas

## **Technical Informations**

Item number	10000633
EAN	4040658104930
Valid tyre size	500 / 80 R 28
LI / SI / PR	164 A8 / 176 A8
TL/TT	TL
Brand	Mitas
Tread pattern	SFT IMP
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	136,00
Recommended rim size	16

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Permitted rim size	15
Maximum air pressure [bar].	3,20
Section width (mm)	517
Outer diameter of tyre [mm].	1495
Stat. radius (SLR) [mm]	635
Rolling circumference [mm].	4355
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 A8	5000	40		3,20	
176 A8	7100	40		3,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.