

TYRES

Product group	Tyres	
Item number	10000636	
Valid tyre size	540 / 65 R 38	
LI / SI / PR	150 A8 / 147 D	
TL/TT	TL	
Brand	Mitas	
Tread pattern	AC 65	
Sonderpostenkategorie	Damaged	
type of damage	Dismounted,Stud damage	



Mitas

Notes and features

- The AC 65 is a powerful all-round wide tyre for use in the field and on the road.
- Thanks to its wide contact area, the soil is protected effectively.
- The wear-resistant rubber compound ensures a long service life.
- The tyre is characterised by a large air volume, guaranteeing a high transport performance.



Technical Informations

Item number	10000636
EAN	4040658104961
Valid tyre size	540 / 65 R 38
LI / SI / PR	150 A8 / 147 D
TL/TT	TL
Brand	Mitas
Tread pattern	AC 65
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	154,00
Recommended rim size	16
Permitted rim size	15, 18
Maximum air pressure [bar].	1,60
Section width (mm)	517
Outer diameter of tyre [mm].	1678
Stat. radius (SLR) [mm]	760
Rolling circumference [mm].	5023
Tread depth (mm)	48,0
Number of lugs	23x2
Lug width (mm)	40
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
150 A8	3350	40		1,60	
147 D	3075	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.