

TYRES

Product group	Tyres
Item number	10000640
Valid tyre size	800 / 70 R 38
LI / SI / PR	181 A8 / 178 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Sonderpostenkategorie	Damaged
type of damage	Dismounted,Stud damage



Mitas

Notes and features

- The Mitas SFT was developed for high-performance machines above 180 hp
- Its big contact area provides excellent traction
- The flexible sidewalls enable high load capacities even at low inflation pressure

Technical Informations

Item number	10000640
EAN	4040658105005
Valid tyre size	800 / 70 R 38
LI / SI / PR	181 A8 / 178 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	373,00
Recommended rim size	25
Permitted rim size	27
Maximum air pressure [bar].	2,40
Section width (mm)	765
Outer diameter of tyre [mm].	2052
Stat. radius (SLR) [mm]	911
Rolling circumference [mm].	6090
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
181 A8	8250	40		2,40	
178 D	7500	65		2,40	