

TYRES

| | |
|-----------------------|-------------------|
| Product group | Tyres |
| Item number | 10000644 |
| Valid tyre size | 480 / 80 R 38 |
| LI / SI / PR | 161 D |
| TL/TT | TL |
| Brand | Nokian |
| Tread pattern | Hakkapeliitta TRI |
| Sonderpostenkategorie | Disassembled |
| type of damage | Dismounted |



nokian®
TYRES

Notes and features

- Innovative winter tyre for tractors.
- Precise steering and efficiency: specially-developed compound for low temperatures and icy surfaces. Revolutionary tread design with sipes and activators.
- First-class ride comfort: low vibration resembling the performance of car and truck tyres.
- Excellent traction and lateral grip: more grip edges in contact with the road surface.
- Evenly-distributed surface pressure ensures good grip.

Technical Informations

| | |
|------------------------------|-------------------|
| Item number | 10000644 |
| EAN | 4040658105043 |
| Valid tyre size | 480 / 80 R 38 |
| LI / SI / PR | 161 D |
| TL/TT | TL |
| Brand | Nokian |
| Tread pattern | Hakkapeliitta TRI |
| M+S | M+S |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 175,43 |
| Recommended rim size | 15 |
| Maximum air pressure [bar]. | 3,20 |
| Section width (mm) | 479 |
| Outer diameter of tyre [mm]. | 1733 |
| Stat. radius (SLR) [mm] | 793 |
| Rolling circumference [mm]. | 5265 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 161 D | 4625 | 65 | | 3,20 | |