

TYRES

Product group	Tyres
Item number	10000648
Valid tyre size	460 / 85 R 38
LI / SI / PR	149 A8 / 149 B
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 85
Sonderpostenkategorie	Damaged
type of damage	Dismounted, Flap damage



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The Traxion 85 is a standard tractor tyre for mid-range tractors.
- Its special tread pattern with curved lugs and rounded shoulders enables high traction while protecting the soil.
- Its flexible casing ensures a big contact area for good ground pressure distribution.
- Its special casing construction with increased volume allows for increased load capacity compared to the older generation standard tyres.
- The bead is reinforced by additional plies, ensuring optimum stability even at higher speeds or on slopes.
- Furthermore, the tyre distinguishes itself through low slip, high ride comfort and a long service life.

Technical Informations

Item number	10000648
EAN	4040658105081
Valid tyre size	460 / 85 R 38
LI / SI / PR	149 A8 / 149 B
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 85
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	149,94
Recommended rim size	DW16L
Permitted rim size	W14, DW14L, W15, DW15L
Maximum air pressure [bar].	1,60
Section width (mm)	490
Outer diameter of tyre [mm].	1750
Stat. radius (SLR) [mm]	815
Rolling circumference [mm].	5205
Tread depth (mm)	48,3
Tyre capacity 75% [ltr.]	365
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A8	3250	40		1,60	
149 B	3250	50		1,60	