

TYRES

Product group	Tyres	
Item number	10000656	
Valid tyre size	650 / 85 R 38	
LI / SI / PR	173 D / 170 E	
TL/TT	TL	
Brand	Trelleborg	
Tread pattern	ТМ900НР	
Sonderpostenkategorie	Damaged	
type of damage	Dismounted,Flap damage	





Notes and features

- The TM 900 High Power was developed specifically for the biggest agricultural machines and high-performance tractors.
- It offers extremely high load capacity.

- Due to its special design, the tyre transmits the vehicle's high torque and enables high traction on all soils.
- It is characterised through extraordinarily high ride comfort and safety.



Technical Informations

Item number	10000656
EAN	4040658105166
Valid tyre size	650 / 85 R 38
LI / SI / PR	173 D / 170 E
TL/TT	TL
Brand	Trelleborg
Tread pattern	ТМ900НР
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	347,00
Recommended rim size	23
Maximum air pressure [bar].	2,40
Section width (mm)	709
Outer diameter of tyre [mm].	2070
Stat. radius (SLR) [mm]	910
Rolling circumference [mm].	6220
Tread depth (mm)	60,0
Lug width (mm)	49
Tyre capacity 75% [ltr.]	1100
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 D	6500	65		2,40	
170 E	6000	70		2,40	_

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.