Bohnenkamp Moving Professionals

13.03.2025

TYRES

Product group	Tyres	
Item number	10000662	
Valid tyre size	580 / 70 R 42	
LI / SI / PR	158 D	
TL/TT	TL	
Brand	Trelleborg	
Tread pattern	ТМ700	
Sonderpostenkategorie	Damaged	
type of damage	Dismounted,Flap damage	





Notes and features

- The TM 700 is an agricultural radial tyre.
- It provides excellent traction in the field and maximum self-cleaning properties, comfort and very good handling on the road.
- Top-level driving performance.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10000662
EAN	4040658105210
Valid tyre size	580 / 70 R 42
LI / SI / PR	158 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	ТМ700
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	233,94
Recommended rim size	18
Maximum air pressure [bar].	1,60
Section width (mm)	584
Outer diameter of tyre [mm].	1908
Stat. radius (SLR) [mm]	864
Rolling circumference [mm].	5690
Tread depth (mm)	58,0
Number of lugs	21x2
Lug width (mm)	60
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 D	4250	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.