

TYRES

| | |
|-----------------------|------------------------|
| Product group | Tyres |
| Item number | 10000667 |
| Valid tyre size | 650 / 85 R 38 |
| LI / SI / PR | 173 D / 170 E |
| TL/TT | TL |
| Brand | Trelleborg |
| Tread pattern | TM900HP |
| Sonderpostenkategorie | Damaged |
| type of damage | Dismounted,Flap damage |



Notes and features

- The TM 900 High Power was developed specifically for the biggest agricultural machines and high-performance tractors.
- It offers extremely high load capacity.
- Due to its special design, the tyre transmits the vehicle's high torque and enables high traction on all soils.
- It is characterised through extraordinarily high ride comfort and safety.

Technical Informations

| | |
|------------------------------|---------------|
| Item number | 10000667 |
| EAN | 4040658105265 |
| Valid tyre size | 650 / 85 R 38 |
| LI / SI / PR | 173 D / 170 E |
| TL/TT | TL |
| Brand | Trelleborg |
| Tread pattern | TM900HP |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 347,00 |
| Recommended rim size | 23 |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 709 |
| Outer diameter of tyre [mm]. | 2070 |
| Stat. radius (SLR) [mm] | 910 |
| Rolling circumference [mm]. | 6220 |
| Tread depth (mm) | 60,0 |
| Lug width (mm) | 49 |
| Tyre capacity 75% [ltr.] | 1100 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 173 D | 6500 | 65 | | 2,40 | |
| 170 E | 6000 | 70 | | 2,40 | |