

TYRES

Product group	Tyres
Item number	10000669
Valid tyre size	520 / 85 R 38
LI / SI / PR	155 A8 / 152 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Sonderpostenkategorie	Damaged
type of damage	Dismounted



Bohnenkamp
Moving Professionals



TRELLEBORG

Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.
- Low soil compaction.
- Optimal traction.

Technical Informations

Item number	10000669
EAN	4040658105289
Valid tyre size	520 / 85 R 38
LI / SI / PR	155 A8 / 152 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	184,36
Recommended rim size	18
Permitted rim size	16
Maximum air pressure [bar].	1,60
Section width (mm)	536
Outer diameter of tyre [mm].	1849
Stat. radius (SLR) [mm]	825
Rolling circumference [mm].	5510
Tread depth (mm)	53,0
Lug width (mm)	51
Tyre capacity 75% [ltr.]	648
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 A8	3875	40		1,60	
152 B	3550	50		1,60	