Bohnenkamp Moving Professionals

05.02.2025

TYRES

Product group	Tyres
Item number	10000670
Valid tyre size	480 / 70 R 30
LI / SI / PR	141 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM700
Sonderpostenkategorie	Damaged
type of damage	Dismounted





Notes and features

- The TM 700 is an agricultural radial tyre.
- It provides excellent traction in the field and maximum self-cleaning properties, comfort and very good handling on the road.
- Top-level driving performance.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10000670
EAN	4040658105296
Valid tyre size	480 / 70 R 30
LI / SI / PR	141 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	ТМ700
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	113,00
Recommended rim size	15
Permitted rim size	14, 16
Maximum air pressure [bar].	1,60
Section width (mm)	468
Outer diameter of tyre [mm].	1474
Stat. radius (SLR) [mm]	667
Rolling circumference [mm].	4425
Tread depth (mm)	52,0
Number of lugs	19x2
Lug width (mm)	49
Tyre capacity 75% [ltr.]	351
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
141 D	2575	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.