

TYRES

Product group	Tyres
Item number	10000673
Valid tyre size	VF 650 / 60 R 38
LI / SI / PR	166 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM1060
Sonderpostenkategorie	Damaged
type of damage	Dismounted, Flap damage



Notes and features

- Innovative tyre for tractors from 80 to more than 300 hp.
- The tyre has innovative double-stacked lugs with two anchor points to increase grip.
- The reinforced lug base significantly reduces vibrations, wear and fuel consumption.
- In addition, these double-edge lugs strengthen the terrace-like lug spaces and thus increase the self-cleaning properties of the tyre.
- Improved pressure range: +0.6 bar enables higher inflation pressure and thus higher payload than other VF/60 tyres present on the market.
- Beside the standard, recommended rims, narrower rims are also permitted.

Technical Informations

Item number	10000673
EAN	4040658105326
Valid tyre size	VF 650 / 60 R 38
LI / SI / PR	166 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM1060
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	222,00
Recommended rim size	23
Permitted rim size	20
Maximum air pressure [bar].	1,60
Section width (mm)	655
Outer diameter of tyre [mm].	1735
Stat. radius (SLR) [mm]	755
Rolling circumference [mm].	5190
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 D	5300	65		1,60	