

## TYRES

|                       |                         |
|-----------------------|-------------------------|
| Product group         | Tyres                   |
| Item number           | 10000673                |
| Valid tyre size       | VF 650 / 60 R 38        |
| LI / SI / PR          | 166 D                   |
| TL/TT                 | TL                      |
| Brand                 | Trelleborg              |
| Tread pattern         | TM1060                  |
| Sonderpostenkategorie | Damaged                 |
| type of damage        | Dismounted, Flap damage |



## Notes and features

- Innovative tyre for tractors from 80 to more than 300 hp.
- The tyre has innovative double-stacked lugs with two anchor points to increase grip.
- The reinforced lug base significantly reduces vibrations, wear and fuel consumption.
- In addition, these double-edge lugs strengthen the terrace-like lug spaces and thus increase the self-cleaning properties of the tyre.
- Improved pressure range: +0.6 bar enables higher inflation pressure and thus higher payload than other VF/60 tyres present on the market.
- Beside the standard, recommended rims, narrower rims are also permitted.

## Technical Informations

|                              |                  |
|------------------------------|------------------|
| Item number                  | 10000673         |
| EAN                          | 4040658105326    |
| Valid tyre size              | VF 650 / 60 R 38 |
| LI / SI / PR                 | 166 D            |
| TL/TT                        | TL               |
| Brand                        | Trelleborg       |
| Tread pattern                | TM1060           |
| Antistatic                   | No               |
| Tyre colour                  | Black            |
| Nettogewicht [kg] (gültig)   | 222,00           |
| Recommended rim size         | 23               |
| Permitted rim size           | 20               |
| Maximum air pressure [bar].  | 1,60             |
| Section width (mm)           | 655              |
| Outer diameter of tyre [mm]. | 1735             |
| Stat. radius (SLR) [mm]      | 755              |
| Rolling circumference [mm].  | 5190             |
| E-Ready                      | No               |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 166 D | 5300               | 65           |               | 1,60                     |              |