

## TYRES

|                 |               |
|-----------------|---------------|
| Product group   | Tyres         |
| Item number     | 10000674      |
| Valid tyre size | 210 / 95 R 16 |
| LI / SI / PR    | 106 D         |
| TL/TT           | TL            |
| Brand           | Alliance      |
| Tread pattern   | Agri Star II  |



## Notes and features

- The Alliance Agri Star II is a new, modern agricultural tractor tyre with speed index "D" (up to 65 km/h) for tractors in all corresponding power ranges.
- The special Stratified Layer Technology provides very good traction and ride comfort in the field and on the road.
- Stratified Layer Technology combines 2 layers of agricultural lugs so that after initial wear of the external lugs, the lower layer of lugs continue to provide traction.
- Even after 40% wear, the 2nd lug layer guarantees good grip and effective traction and thus a long service life.
- The wide contact area ensures low soil compaction.
- The special abrasion- and puncture-resistant rubber compound (Stubble Guard) protects the tyre from damage caused by grain stubble.

## Technical Informations

|                              |               |
|------------------------------|---------------|
| Item number                  | 10000674      |
| EAN                          | 8903635051008 |
| Valid tyre size              | 210 / 95 R 16 |
| LI / SI / PR                 | 106 D         |
| TL/TT                        | TL            |
| Brand                        | Alliance      |
| Tread pattern                | Agri Star II  |
| TRA Code                     | R1            |
| Carcass properties           | Stubble Guard |
| Antistatic                   | No            |
| Tyre colour                  | Black         |
| ECE regulation number        | ECE 106       |
| Nettogewicht [kg] (gültig)   | 21,34         |
| Recommended rim size         | 7             |
| Maximum air pressure [bar].  | 2,40          |
| Section width (mm)           | 214           |
| Outer diameter of tyre [mm]. | 806           |
| Stat. radius (SLR) [mm]      | 365           |
| Rolling circumference [mm].  | 2381          |
| E-Ready                      | No            |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 106 D | 950                | 65           |               | 2,40                     |              |