

TYRES

Product group	Tyres	
Item number	10000679	
Valid tyre size	520 / 70 R 38	
LI / SI / PR	150 D	
TL/TT	TL	
Brand	Trelleborg	
Tread pattern	TM700	
Sonderpostenkategorie	Damaged	
type of damage	Dismounted,Puncture at tyre shoulder	





Notes and features

- The TM 700 is an agricultural radial tyre.
- It provides excellent traction in the field and maximum self-cleaning properties, comfort and very good handling on the road.
- Top-level driving performance.



Technical Informations

Item number	10000679
EAN	4040658105388
Valid tyre size	520 / 70 R 38
LI / SI / PR	150 D
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM700
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	161,50
Recommended rim size	16
Permitted rim size	15, 18
Maximum air pressure [bar].	1,60
Section width (mm)	520
Outer diameter of tyre [mm].	1740
Stat. radius (SLR) [mm]	774
Rolling circumference [mm].	5150
Tread depth (mm)	55,0
Number of lugs	20x2
Lug width (mm)	53
Tyre capacity 75% [ltr.]	507
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
150 D	3350	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.