

TYRES

Product group	Tyres
Item number	10000686
Valid tyre size	710 / 45 - 26.5
LI / SI / PR	168 A8, 20PR
TL/TT	тт
Brand	Alliance
Tread pattern	Forestar 643 III





Notes and features

- The Alliance Forestar 643 III is a forestry tyre for timber transporters, timber harvesting vehicles and trailers.
- Its special tread pattern is ideal for combining with chains.
- But even without chains, this tyre offers very good grip even under difficult conditions in the forest.
- Thanks to its outstanding stability, good self-cleaning properties and robust construction, the tyre is ideally suited for forestry use.



Technical Informations

Item number	10000686
EAN	8903635022916
Valid tyre size	710 / 45 - 26.5
LI / SI / PR	168 A8, 20PR
TL/TT	тт
Brand	Alliance
Tread pattern	Forestar 643 III
TRA Code	LS-2
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	229,20
Recommended rim size	AG24.00
Maximum air pressure [bar].	5,00
Section width (mm)	695
Outer diameter of tyre [mm].	1340
Stat. radius (SLR) [mm]	623
Speed Radius Index (SRI)	650
Rolling circumference [mm].	4126
Contact area [cm²]	1665.2
Tread depth (mm)	38,0
Number of lugs	17x2
Tyre capacity 75% [ltr.]	425
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 A8	5600	40		5,00	